

## IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

### *Listing of Claims*

1-4. (Canceled)

5. (Currently Amended) ~~A computer-readable storage medium configured to store a data structure, the data structure~~ method of performing a route lookup based on a received IP destination address, the method comprising:

configuring a first lookup table having at least one entry, each of the at least one entry

having a bitmap portion and an information storage portion;

configuring a second lookup table having at least one entry, each entry in the at least one entry storing next hop and prefix length information; and

configuring a third lookup table having at least one entry, the at least one entry including a pointer portion and a variable value K,

wherein the configuring steps are performed such that each at least one entry of the third

lookup table is indexable by a segment portion of the IP destination address, and

wherein when there is a route having a prefix matching the index of the at least one

entry and a prefix length greater than a predetermined value, the pointer portion

includes a pointer that is combined with K bits of the IP destination address following

the segment portion to determine an index for the at least one entry in the first lookup table,

wherein bits within the bitmap of the at least one entry are indexable by a second portion of the IP destination address,

the information storage portion of each of the at least one entry stores next hop and prefix information when the total number of ones in the bitmap of the at least one entry is one of a given set of values, and

the information storage portion of each of the at least one entry information pointing to an entry in the second lookup table when the total number of ones in the bitmap of the at least one entry is not one of the given set of values.

6. **(Currently Amended)** The ~~storage-medium~~ method of claim 5, wherein the first set of values includes one and two.

7. **(Currently Amended)** The ~~storage-medium~~ method of claim 6, wherein the configuring steps are performed such that:

the information storage portion of the at least one entry stores one set of next hop and prefix length information when the total number of ones in the bitmap of the at least one entry is one;

the information storage portion of the at least one entry stores two sets of next hop and prefix length information when the total number of ones in the bitmap of the at least one entry is two; and

the information storage portion of the at least one entry stores information pointing to an entry in the second lookup table when the total number of ones in the bitmap of the at least one entry is more than two.

8. **(Currently Amended)** A method ~~of storing information in the data structure of~~ according to claim 5, the method comprising wherein the configuring steps further include:

determining for each entry in a group of entries in ~~a data structure~~ the lookup tables,

whether a value of the entry is different from a value of a previous entry,

when the entry value is different from the previous entry value, storing a first bit value in a corresponding place in a bitmap corresponding to that group of entries; and

when the entry value is the same as a previous entry value, storing a second bit value different from the first bit value in the corresponding place;

when a number of ones in the bitmap is in a first set of values, storing next hop and prefix length information in an entry storing the bitmap, the next hop and prefix length information corresponding to entries in the bitmap; and

when a number of ones in the bitmap is in a second set of values, storing an index to next hop and prefix length information corresponding to the bitmap information stored in a second data structure in the entry storing the bitmap.

9-13. **(Canceled)**

14. (Previously Presented) A method of updating a data structure suitable for use in a route lookup system in a communications network, the method comprising:

receiving an IP route having an IP address component, prefix length component and next hop component;

checking a group of entries in a data structure indicated by the prefix length component, the group having a size determined by a length of the IP address less the prefix length; and

performing a longest match procedure to update the group of entries to have most specific next hop and prefix length information for the group of entries, wherein updating includes determining and storing a variable value K in the data structure, and further including storing next hop and prefix information for certain of the updated group of entries entirely within a  $2^K$  block of entries in another data structure;

wherein checking includes

determining whether a given portion of an entry in the group of entries stores next hop and prefix information, or stores an index to a block of next hop and prefix information in the another data structure; and

obtaining prefix length and next hop information for the entry based on the determination result.

15-16. **(Canceled)**

17. **(Currently Amended)** The ~~storage-medium~~ method of claim 5, wherein K is less than a total number of bits of the IP destination address less a number of bits comprising the segment portion.